



BMZ GmbH
Am Sportplatz 28
63791 Karlstein am Main
Germany
Phone +49 6188-9956-0
Fax +49 6188-9956-900
sales.ESS@bmz-group.com
www.bmz-group.com
Servicekontakt: CS.BigPack@bmz-group.com

BMZ Japan KK
Takano 2-436,
Misato, Saitama,
341-0035 Japan
Phone +81 (0) 48 951 4065
Tokio.Kobayashi@bmz-group.com

BMZ Company Ltd.
2nd Building, NO.2 Jinlong Street
Baolong Industry Zone, Longgang
518116 Shenzhen / China
Phone +86 755 89775-800
Fax +86 755 89775-900
sales@bmz-group.com

BMZ USA Inc.
2656 Lishelle Place
Virginia Beach, VA 23452
USA
Phone +1 757 821-8494
Fax +1 757 821-8499
info@bmz-usa.com
www.bmz-usa.com

BMZ Poland Sp.z.o.o.
Alberta Einsteina 9
44-109 Gliwice
Poland
Phone +48 327842 450
Fax +48 327842 451
biuro@bmz-group.com

BMZ France S.A.R.L.
45 Boulevard Vincent Auriol
75013 Paris
France
Phone +33 (0) 9 51 00 7579
jean-marc.brunet@bmz-group.com

PREFACE

ESS 7.0/9.0/X is a new modular lithium-ion based energy storage system, which stores the surplus of the collected solar energy for later use. Energy can either be directed into the storage system or be fed into the public grid via an inverter.

Energy is available as required: in the evening, at night, or on a cloudy day.

With the ESS 7.0/9.0/X System, consumers of solar power become more independent from electricity prices and use their home-made eco-electricity when they need it.

ADVANTAGES

- Technical service online and by telephone
- Store during the day; use day and night
- Independent from daylight and public grid
- Economic, cost-cutting and ecofriendly
- Robust, safe and space saving
- Modular installation: the storage capacity can be adapted to your needs
- Subsidized by the Federal Government of Germany: KfW-Program 275

TECHNICAL PROPERTIES

- Powerful energy storage system
- New lithium-ion technology: a 10 year warranty covering the system's current value (not in all countries)
- High efficiency: 95 %
- High discharge depth: 80 % DOD (Depth of Discharge)
- Durable: 5,000 full cycles
- Parallel installation of max. 12 modules possible
- High operational safety

SAFETY MEASURES

- Direct current relay and 2nd protection (chemical fuse) for a redundant battery cut-off
- Overvoltage and low voltage monitoring for each cell string with redundant battery cut-off
- Temperature monitoring for each cell string
- Current interrupt device (CID) in each cell
- Protection against a reboot after deep discharge or any other serious error
- Active current control as a function of cell voltage and temperature (derating)
- Closed metal, double housing

TECHNICAL PROPERTIES OF A SINGLE MODULE

GENERAL PROPERTIES	ESS 7.0	ESS 9.0	ESS X
Energy (nom./usable)	6.74 kWh/5.39 kWh	8.5 kWh/6.8 kWh	10.06 kWh/8.05 kWh
Nominal voltage	55.5 V	54.0 V	54.0 V
Charge end voltage	61.5 V	61.5 V	61.5 V
Discharge end voltage	45.0 V	45.0 V	45.0 V
Capacity (nom./usable)	121.5 Ah/ 97.2 Ah	156.6 Ah/125.3 Ah	186.3 Ah/149.1 Ah
Max. charge	90 A	90 A	90 A
Max. discharge current	300 A (3 sec)	300 A (3 sec)	300 A (3 sec)
Max. discharge power	18 kW*	18 kW*	18 kW*
Weight	95 kg	97 kg	99 kg
Dimensions (W x H x D)	638 x 421 x 487 mm	638 x 421 x 487 mm	638 x 421 x 487 mm
Communication	CAN – SMA ready	CAN – SMA ready	CAN – SMA ready
Battery chemistry	Li-Ion NMC	Li-Ion NCA	Li-Ion NCA
Discharge depth	80% DOD	80% DOD	80% DOD
Full cycles	5,000	5,000	5,000
Battery Management System	Monitoring of cell voltage, cell temperature, current, derating and passive balancing		

PERFORMANCE DATA

Energy density (weight)	71 Wh/kg	87.6 Wh/kg	101.6 Wh/kg
-------------------------	----------	------------	-------------

DEVELOPED ACCORDING TO THE STANDARDS AND USER GUIDELINES FOR STATIONARY ENERGY STORAGE SYSTEMS

- VDE-AR-E 2510-50
- VDE-AR-E 2510-2
- DIN EN 62619 (draft)
- FNN note (04/2016 version)

USER INFORMATION

- Discharge temperature (cells): 2 °C to +45 °C
- Charge temperature (cells): 2 °C to +45 °C
- Recommended storage temperature: 10 °C to 25 °C
- Self discharge (cells): ca. 2 % per year
- Stand-by consumption: Active mode 5 W / Sleep mode 0.126 W
- Max. parallel connection (of batteries): 12 (additional hardware required)
- Protection class: IP 21
- European Conformity (CE): yes
- UN-test 38.3: yes
- Warranty: 10 year warranty covering the system's current value (not in all countries)



ESS 7.0/9.0/X

*depends on the respective inverter